In two Sheets. Sheet No. 1

1878

MAP OF MOUTH OF COHANSEY RIVER, N. J.

From Survey of November, 1905,
made in accordance with Sec 9,
of the River and Harbor act of March 3, 1905.
Scale: 1in = 300ft.

Bench Mark on highest point of U.S.L.H.E. Reservation Stone about 200ft. N. from Cohansey Light House at mouth of Cohansey River Elevation above M.L.W. 8.40 feet.

NOTE

The soundings are expressed in feet and tenths and show the depths at mean low water.
The mean low water line is shown thus: .....
" 6 foot curve of depth is " " " " —— —— ——
" 12 " " " " " " —— —— ——
" 18 " " " " " " —— —— ——
" 24 " " " " " " —— —— ——
" 7 " " " " " " —— —— ——
" 8 " " " " " " —— —— ——
" mean rise of tide is 5.5 feet.
Proposed Cut-off shown thus: ////////

P.F. Causey, Jr. Surveyor.
Eugene Reybold, Draftsman.

COHANSEY RIVER

DELAWARE BAY

CARNELL

UNITED STATES RESERVATION

COHANSEY LIGHT

STONE MONUMENT MARKED U.S.L.H.E.

E. JACKSON

3200.00ft.

1800.00ft.

ARC 1000ft.

U.S. Engineer Office,
Wilmington, Del.

To accompany project and estimate
dated Feb. 21, 1906.

C A Flagler
Captain Corps of Engineers, U.S.A.

Retraced from Blue Print
W.E.S. 3-7-07