

List of Figures

Figure 1: The Swarm Manned Aerial Vehicle Multirotor Super Drone Flying	2
Figure 2: Air Flow Through a Single Rotor and a Coaxial Rotor System	5
Figure 3: Helicopter and Propeller Blade Shape Comparison	7
Figure 4: Diagram of Airflow between a Single Rotor and Coaxial Rotors	9
Figure 5: Diagram of the Experimental Equipment Setup	12
Figure 6: Diagram of the Naming Convention of Coaxial Rotor Combinations	14
Figure 7: Individual Propellers	17
Figure 8: Performance and Thrust of 10” Propellers	19
Figure 9: Performance and Thrust of 13” Propellers	20
Figure 10: Performance and Thrust of 15” Propellers	21
Figure 11: Varying Orientation and Spacing Between 10” Propellers	22
Figure 12: Varying Orientation and Spacing Between 13” Propellers	23
Figure 13: Varying Orientation and Spacing Between 15” Propellers	24
Figure 14: Thrust Capacity of Constant Diameter Systems	25
Figure 15: Thrust Output of Constant Diameter Systems	28
Figure 16: 13”-Propeller-Led Systems at 3” Separation	29
Figure 17: 13”-Propeller-Led Systems at 6” Separation	30
Figure 18: 13”-Propeller-Led Systems at 9” Separation	31
Figure 19: Increasing vs Constant Diameter Propeller Systems	33
Figure 20: Max Thrust Capacity of Constant and Increasing Diameter Systems	34

Figure 21: Decreasing vs. Constant Diameter Propeller Systems	36
Figure 22: Max Thrust Capacity of Constant and Decreasing Diameter Systems	37
Figure 23: Trios of Increasing and Constant Diameter Propellers	38
Figure 24: Max Thrust of Increasing Coaxial Trio and Separate Propellers	39
Figure 25: Decreasing Diameter 15R-13L-10R Configuration	41
Figure 26: Thrust Output of Pairs with Separately Controlled Inputs	43
Figure 27: Performance of Pairs with Separately Controlled Inputs	44
Figure 28: Vibration of 13R-15R at 6" Separation	45
Figure 29: Vibration of 13R-15R at 9" Separation	45
Figure 30: Thrust Output of Systems with Separate and Shared Inputs	46
Figure 31: Choosing a System with a Spatial Limit of 10 Inches	48
Figure 32: Choosing a System with a Spatial Limit of 13 Inches	49
Figure 33: Choosing a System with a Spatial Limit of 15 Inches	51
Figure 34: Thrust Capacity vs Obscured Area	53